

FUJIFILM

X | GFX



*X half*  
HALF THE SIZE,  
TWICE THE STORY



*X half*  
HALF THE SIZE,  
TWICE THE STORY



ULTRA-LIGHT  
**240G\***  
CLASSIC DESIGN

UNIQUE  
**2-IN-1**  
FEATURE

WIDE-ANGLE  
**32MM F2.8**  
PRIME LENS

1-INCH  
**3:4 VERTICAL**  
SENSOR



### CLASSIC DESIGN

- Aperture Ring and Exposure Comp. Dial
- Tactile Frame Advance Lever
- Vertical Viewfinder and Rear LCD
- Ultra-light and Compact (240g)



### 1-INCH SENSOR + 32MM\* PRIME LENS

- 3:4 Vertical Framing, date stamp feature
- Fast AF with Face and Eye Detection
- Rechargeable Li-ion Battery, 880 frames\*<sup>2</sup>
- Built-in LED Flash



### FILM PHOTOGRAPHY IN A DIGITAL WORLD

- Film Camera Mode for a more analog experience
- Sub-LCD for Film Simulation / Filter Effects
- 2-in-1 feature combines 2 vertical frames
- Seamless Printing with instax™ Link Series



### CREATE YOUR OWN STORY

- 13 Film Simulations
- Light leaks, halation, expired film, double exposure, retro, and other analog-inspired filters
- Grain Effect adds film-like grain to your images



### SOCIAL MEDIA READY VIDEO

- 1080/24P video with small file sizes
- Create movies using Film Simulation or Filter Effects
- Up-to 200% Slow-motion recording
- Includes USB-C to 3.5mm Headphone adapter



### DEDICATED X HALF APP (IOS AND ANDROID)

- Transfer images to your smartphone
- Create 2-in-1 with your favourite frames
- Create a personalized Gallery and Album
- Develop your film roll. Incl. contact sheet

\*1 including battery and SD card  
\*2 OVF - Normal mode



*X half*  
HALF THE SIZE,  
TWICE THE STORY



## COLOURS



BLACK  
MSRP: \$998.99



CHARCOAL SILVER  
MSRP: \$998.99



SILVER  
MSRP: \$998.99

## INCLUDED IN THE BOX

LI-ION BATTERY NP-W126S, HEADPHONE ADAPTER, HAND STRAP, LENS CAP, COLD SHOE COVER, METAL STRAP CLIP, PROTECTIVE COVER

## ACCESSORIES



LI-ION BATTERY NP-W126S  
MSRP: \$100



INSTAX MINI LINK 3 PRINTER  
MSRP: \$129




INSTAX SQUARE LINK PRINTER  
MSRP: \$179



INSTAX LINK WIDE PRINTER  
MSRP: \$189



*X half*  
HALF THE SIZE,  
TWICE THE STORY



## FILM CAMERA MODE

To activate FILM CAMERA MODE, swipe down on the LCD and select it. Choose the number of shots, whether to include date/time, and your exposure mode. Press Start, then activate the frame advance lever to take your first photo. Be sure to advance the lever before each shot. To end your roll early, double tap the sub LCD and select END MID ROLL. When finished, pair the camera with the X Half app to develop your roll and receive a contact sheet.

## 2-IN-1 MODE

The X half features a 2-in-1 mode that lets you combine two frames, videos, or a mix of both. To activate it, push the frame advance lever—your next shot will be combined with the previous one. To cancel, pull the lever again. While framing your next shot, press the lever inward to preview the previous image.



## SEAMLESS PRINTING WITH INSTAX™ LINK SERIES

To print from the X half to an instax Link printer, turn on the printer and swipe down on the camera's LCD. Select Pairing — the printer will be detected automatically. In playback mode, select an image and tap the MENU icon. Choose between Natural or Rich mode, then select instax PRINTER PRINT. Swipe to the image, press OK, reframe by pinching or rotate using the rotate button. Tap the print icon to send the image to the printer.



## EXPOSURE CONTROLS

Swipe left on the camera's LCD to access the menu. Select EXPOSURE MODE to choose between Program Auto, Shutter Priority, Aperture Priority, or Manual. Use the aperture ring on the lens to adjust aperture. In Manual mode, tap ISO or Shutter Speed on the LCD to adjust settings. In Auto or Semi-Auto modes, use the exposure compensation dial to brighten or darken the image.



*X half*  
HALF THE SIZE,  
TWICE THE STORY

LEARN  
MORE



## 2-IN-1 CUSTOM SETTINGS

To customize the 2-in-1 feature, swipe left on the camera's LCD. On the sub LCD, scroll down to the SETUP menu and select CUSTOM SETTING. You can customize the dividing lines, the order of the 2-in-1 photos, whether you want the date stamp ON or OFF on both photos and videos, and the color of the contact sheet's background



*X half*  
HALF THE SIZE,  
TWICE THE STORY



## SPECIFICATIONS

**FUJIFILM**  
X | GFX

<b>Model Name</b>	FUJIFILM X half
<b>Number of effective pixels</b>	17.74 million pixels
<b>Image Sensor</b>	13.3mm x 8.8mm (1 inch) with primary color filter
<b>Storage media</b>	SD memory card (~2GB) / SDHC memory card (~32GB) / SDXC memory card (~512GB) UHS-I *Please see the Fujifilm website ( <a href="https://fujifilm-x.com/support/compatibility/cameras/">https://fujifilm-x.com/support/compatibility/cameras/</a> ) to check memory card compatibility.
<b>File format of still image</b>	DCF Compliant with Design rule for Camera File system (DCF2.0) JPEG Exif Ver.2.31 *1
<b>Lens Type</b> <b>Focal length</b> <b>Max aperture</b> <b>Lens configuration</b>	FUJINON single focal length lens f=10.8mm (35mm format equivalent : 32mm) F2.8 6 elements in 5 groups (includes 3 aspherical elements)
<b>Aperture</b>	F2.8- F11 1/3EV step (controlled with 3-blade aperture diaphragm)
<b>Minimum focus distance (from the front of the lens)</b>	Approx. 0.1m
<b>Sensitivity Standard output</b>	AUTO1 / AUTO2 / AUTO3 / ISO200 to 12800(1/3 step)
<b>Exposure mode</b>	P (Program AE) / A (Aperture Priority AE) / S (Shutter Speed Priority AE) / M (Manual Exposure)
<b>Exposure compensation</b>	Still: -3.0EV~+3.0EV 1/3EV step Movie: -2.0EV~+2.0EV 1/3EV step
<b>Shutter type</b>	Lens Shutter
<b>Movie recording File Format</b> <b>File size</b> <b>Frame rate</b> <b>Bitrate</b> <b>Highspeed</b>	H.264 Long GOP 4:2:0 MOV, H.264 Long GOP 4:2:0 MP4 Full HD 24p 10Mbps, 20Mbps, 50Mbps Full HD, 48fps (2x), 36fps (1.5x), 28fps (1.2x), H.264 Long GOP 4:2:0 MOV, H.264 Long GOP 4:2:0 MP4, 10Mbps, 20Mbps, 50Mbps
<b>Flash</b>	LED
<b>LCD monitor</b>	2.4 inch Touch Screen Color LCD Monitor, 4:3, approx. 0.92 million dots
<b>Viewfinder OVF</b> <b>Coverage of Frame Area</b> <b>Magnification</b>	Reverse Galilean viewfinder Approx. 90% approx x0.38
<b>Film Simulation modes</b> <b>Filters</b>	PROVIA/Standard, Velvia/Vivid, ASTIA/Soft, Classic Chrome, REALA ACE, Classic Neg., Nostalgic Neg., ETERNA/Cinema, ACROS, ACROS + Ye Filter, ACROS + R Filter, ACROS + G Filter, Sepia Toy camera, Miniature, Pop color, High-key, Low-key, Dynamic tone, Soft focus, Partial color (Red / Orange / Yellow / Green / Blue / Purple), LIGHT LEAK, HALATION, EXPIRED FILM (Green / Red/ Neutral), Canvas, Retro, Vignette, Blur, Fisheye, ColorShift, Mirror, Double Ex.
<b>Dimensions</b>	Width: 105.8mm Height: 64.3mm Depth: 30.0mm
<b>Weight</b>	Approx. 240g (including battery and SD memory card) Approx. 191g (excluding battery and SD memory card)
<b>Notes</b>	*1 Exif 2.31 is a digital camera file format that contains a variety of shooting information for optimal printing.

# FUJIFILM

---

## X | GFX



📷 📺 FUJIFILMX\_CA

VISIT [WWW.FUJIFILM-X.COM](http://WWW.FUJIFILM-X.COM) OR YOUR AUTHORIZED DEALER FOR MORE INFORMATION.

FUJIFILM and FUJINON are trademarks of FUJIFILM Corporation and its affiliates. © 2025 FUJIFILM North America Corporation and its affiliates. All rights reserved.